

## POWER TRANSFER HINGE



### Specification

| P/N Hinge | Hinge Size(INCHES) | Hinge Size (mm) | Thickness (mm) | Hole count | Screw Size (Machine) | Screw size (wood) | Bearings Count |
|-----------|--------------------|-----------------|----------------|------------|----------------------|-------------------|----------------|
| 2BB4W4540 | 4.5 x 4.0          | 114 x 102       | 3.4            | 8          | 1/2 x 12-24          | 1-1/4 x 12        | 2              |
| 2BB4W4545 | 4.5 x 4.5          | 114 x 114       | 3.4            | 8          | 1/2 x 12-24          | 1-1/4 x 12        | 2              |
| 2BB4W5045 | 5.0 x 4.5          | 127 x 114       | 3.4            | 8          | 1/2 x 12-24          | 1-1/4 x 12        | 2              |
| 2BB8W4540 | 4.5 x 4.0          | 114 x 102       | 3.4            | 8          | 1/2 x 12-24          | 1-1/4 x 12        | 2              |
| 2BB8W4545 | 4.5 x 4.5          | 114 x 114       | 3.4            | 8          | 1/2 x 12-24          | 1-1/4 x 12        | 2              |
| 2BB8W5045 | 5.0 x 4.5          | 127 x 114       | 3.4            | 8          | 1/2 x 12-24          | 1-1/4 x 12        | 2              |

### Features

- Compatible with electrified locks, electric strikes, exit devices.
- With 5 knuckles and 2 ball bearings.
- The maximum voltage allowed in electrified hinge is 50V, 3.5A
- Available for Square corner and radius corner
- Other requirement of numbers of wires hinges is available.

### Material

- Stainless Steel with steel pin

### Certificates

- ANSI/BHMA A156.1
- UL10C
- It passes salt spray test 200 hours.